

真空填料机 Hopper Loaders

■ 直结式真空填料机特点 Features

- ◆体积小、重量轻，可直接放置在干燥机或其他原料容器上，完成自动上料。
- ◆微电脑控制，操作简易。
- ◆过载、缺料报警。
- ◆300系列采用碳刷式马达，体积小、吸力强，适合新料输送。
- ◆配有集尘袋，免拆主机清理。
- ◆配有空气滤清器。
- ◆Small footprint & light, to be placed directly on other machine or container for auto loading.
- ◆Microprocessor controlled for ease of use.
- ◆Alarm for overload and lack of material.
- ◆GAL-300 series adopt carbon brush motor, small, strong suction power, suitable for deferent type of new materials.
- ◆Equipped with dust collector to save dismantling mainframe for cleaning.
- ◆Installed with air filter.



■ 分离式真空填料机特点 Features

- ◆微电脑控制，操作简易。
- ◆过载、缺料报警。
- ◆采用感应式高压风机，噪音小，寿命长(700G采用碳刷式马)。
- ◆不锈钢料斗，确保原料不受污染。
- ◆主机与料桶分离设计，安全简便。
- ◆独立滤清器装置，方便清除积尘。
- ◆Microprocessor controlled for ease of use.
- ◆Alarm for overload and lack of material.
- ◆They are equipped blower with high efficiency and high pressure, light weight, durable, great suction power, easy installation and operation(GAL-700G series adopt carbon brush motor).
- ◆Stainless hopper receiver ensure no contamination.
- ◆Main unit and hopper designed separated, to ensures safety and convenient.
- ◆Separate filter installed, easy to remove pooling of powder.



■ 机型规格 Specifications

主机 Main Unit					料斗 Hopper Receiver				输料管径 Conveying Pipe Dia. (inch)	输送能力 Conveying Capacity (kg/hr)
机型 Model	马达形式 Motor Type	马达功率 Motor Power (kw)	外形尺寸 Dimensions H*W*D (mm)	净重 Weight (kg)	可选型号 Recommended Model	料斗容量 Hopper Capacity	外形尺寸 Dimensions H*W*D (mm)	净重 Weight (kg)		
SAL-300G	碳刷式 (Carbon Brush)	1.1 (1Φ)	590*340*340	13	-	7.5	-	-	1.5"	200
SAL-700G	碳刷式 (Carbon Brush)	1.1 (1Φ)	590*300*390	30	GMH-6L	7.5	450*260*300	6	1.5"	300
					GVH-6L	7.5	585*260*330	7	1.5"	300
SAL-800G	感应式 (Induction)	1.1 (3Φ)	660*370*420	44	GMH-6L	7.5	450*260*300	6	1.5"	300
					GVH-6L	7.5	585*260*300	7	1.5"	300
SAL-800G2	感应式 (Induction)	1.5 (3Φ)	660*370*420	44	GMH-12L	12	530*310*350	7	1.5"	550
					GVH-12L	12	680*310*350	10	1.5"	400
SAL-900G	感应式 (Induction)	1.1 (3Φ)	680*375*740	46	GMH-6L*1	7.5	450*260*300	6	1.5"	450
					GVH-6L*1	7.5	585*260*300	7		
					GMH-6L*2	7.5	450*260*300	6	1.5"	700
					GVH-6L*2	7.5	585*260*300	7		
SAL-900G2	感应式 (Induction)	1.5 (3Φ)	680*375*740	46	GMH-12L*1	12	530*310*350	7	1.5"	700
					GVH-12L*1	12	680*310*350	10		
					GMH-12L*2	12	530*310*350	7	1.5"	700
					GVH-12L*2	12	680*310*350	10		

注：1) "GMH" 表示真空料斗，"GVH" 表示光电料斗。2) 输送能力测试条件：垂直高度4m。3) 机器电压规格：SAL-300G和SAL-700G为1Φ,220V,50HZ; 其余机型皆为3Φ,380V。
 Note: 1)"GMH" stands for vacuum hopper receiver, "GVH" stands for photosensor hopper receiver. 2) Test of condition of conveying capacity: vertical conveying height: 4m.
 3) Power Supply: 3Φ, 380VAC (Except GAL-300 and GAL-700G), 50Hz.